

MXG2PRDREM

3.5" MX G2 LED Downlight Cylinder With Remote Driver Enclosure

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

ELECTRICAL DATA

LED Light Engine	System Wattage *	CCT / CRI	Delivered Lumens **
L0	10W	3000K / 82 CRI	900lm
L1	16W	3000K / 82 CRI	1300lm
L2	20W	3000K / 82 CRI	1525lm

* System Wattage includes driver and LED Module consumption.

** Delivered lumens will vary depending on trim, CCT, CRI, optic and ceiling thickness

FEATURES

- Sleek, high performance pendant complements MX downlighting family
- Offered in various mounting options including cable, stem and surface
- Utilizes MX trims to ensure aesthetic consistency across the product line
- Unique flush, surface mount design allows for precise alignment and adjustment
- Dedicated 9° optic with field changeable 12°, 24°, 36° & 50° optics

LED LIGHT ENGINE

- 92 CRI & 82 CRI in 2700K, 3000K, 3500K and 4100K with 2 SDCM binning
- >50,000 hours L70 (rated life at 70% output)

ELECTRICAL SYSTEM

- 120/277V 50/60Hz input
- Class 2 power supply
- Over voltage/current and short circuit protection with auto recovery

EMERGENCY BACKUP

Remote test switch included. External battery operates LED load of up to 7W at a minimum of 400 lumens for 90 minutes (EM7).

DIMMING

- Forward/reverse phase dimming 1% (120V only)
- 0-10V Dimming 1%
- eldoLED 0-10V 0.1% or 1%
- Lutron® LDE1 Hi-Lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology
- DMX512 RDM 0.1%

MOUNTING

- Mounts to 4" octagon J-Box with raised fixture cover (supplied by others)
- Pendant stems supplied with complete canopy assembly
- Cable / pendant mount are matched to housing finish

TRIM SPECIFICATION

High quality trims are die-cast using A380 aluminum with durable powder coat available in multiple finishes.

REMOTE DRIVER ENCLOSURE

- Galvanized steel construction
- 50ft remote distance maximum

ACCESSORIES

Luminaire will accommodate (2) accessories, accessory holder required. Accessory holder not compatible with lensed trims

LLISTING / WARRANTY


- ETL Listed to US and Canadian standards for damp locations
- ETL Listed to US and Canadian standards for wet locations when used surface mount option only
- 5-Year Intense LED Limited Warranty



MX



Pendant Size Options



(See Page 2 For Dimensions)

Available Trim Finishes



Cylinder Part Number (Example: MXG2PRDREM2L130912WWR12)

Cylinder	Height	Wattage	CCT / CRI	Optic	Housing Finish	Trim Finish	Lens	Mounting
MXG2PRDREM	1 (9")	L0 (10 Watts)	27 (2700K / 82 CRI)	09 ¹ (9° Narrow Spot)	B (Black)	B (Black)	blank (None)	C48 (48" Cable)
		L1 (16 Watts)	279 (2700K / 92 CRI)	12 (12° Spot)	W (White)	W (White)	SL ² (Solite)	C96 (96" Cable)
	2 (12")	L2 (20 Watts)	30 (3000K / 82 CRI)	24 (24° Narrow Flood)	SN (Satin Nickel)	CR ² (Clear)	R12 (12" Rigid Pendant)	
		30 (3000K / 92 CRI)	36 (36° Flood)	AB (Antique Bronze)	FR ² (Frosted)	R24 (24" Rigid Pendant)		
		35 (3500K / 82 CRI)	50 (50° Wide Flood)	R36 ⁶ (36" Rigid Pendant)				
		359 (3500K / 92 CRI)	R48 (48" Rigid Pendant)					
		41 (4100K / 82 CRI)	S ⁷ (Surface)					
		419 (4100K / 92 CRI)						

Remote Emergency Power Box (Example: REMMXG2PLOEM7)

Power Box	Wattage	Dimming	Emergency Back Up
REMMXG2P	L0 (10 Watts)	blank (Non-Dimming)	EM7 (7W Emergency Backup IOTA part #ILB-CP07-A)
	L1 (16 Watts)	-DELV ³ (Full Phase Dimming)	
	L2 (20 Watts)	-D101 (0-10V Dimming 1%)	
		-ED10V1 (eldoLED 0-10V 1%)	
		-ED10V01 (eldoLED 0-10V 0.1%)	
		-LUT ⁴ (Lutron® LDE1 EcoSystem 1%)	
-DMXR (DMX512 RDM 0.1%)			

Notes:

1. 9° Narrow spot not available in L2. Available with 279 only.
2. Accessories holder not compatible with lensed trims
3. Available only in 120V
4. Not available in L2
5. Special order, consult factory for lead times
6. Special order. Note: 36" Pendant is made with (1) 12" & 24" w/ coupler
7. Surface mount can be used in wet locations, see instruction sheet for proper installation instructions

Accessories²

LH47	(Accessory Holder, Black)
LH47W	(Accessory Holder, White)
PFLM-47	(Hex Louver, Black)
PFL1-47	(Prismatic Spread Lens)
PFL2-47	(Linear Spread Lens)
PFL4-47	(Solite Lens)

MX PENDANT L/M-0522-25 P-1

INTENSE LIGHTING | 725 Landwehr Road, Northbrook, IL 60062 | tel 714 630-9877 | fax 847 559-5505

For Intense Lighting's limited product warranty, go to www.intenselighting.com. For a printed copy of the warranty, you may call 714 630-9877.


© 2025 Intense Lighting, LLC. All rights reserved. Note: This document is subject to change without notice.

MXG2PRDREM


3.5" MX G2 LED Downlight Cylinder With Remote Driver Enclosure

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	


Surface Mount




Rigid Pendant Mount




Cable Mount



Remote Driver Enclosure



Emergency Backup




JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

MXG2PRD3L030

Report #: ILL-20170427-03.001 (12)
 ILL-20170427-01.001 (24)
 ILL-20170427-04.001 (36)
 ILL-20170427-02.001 (50)

CCT MULTIPLIERS:

	82 CRI	92 CRI
2700K	(x 0.93)	(x 0.76)
3000K	(x 1.00)	(x 0.87)
3500K	(x 1.00)	(x 0.87)
4100K	(x 1.00)	(x 0.87)



Intensity	
Degree	CBCP
0°	12263
5°	8719
15°	402
25°	95
35°	27
45°	3

Intensity	
Degree	CBCP
0°	5536
5°	4868
15°	1436
25°	196
35°	13
45°	2

Intensity	
Degree	CBCP
0°	2286
5°	2194
15°	1421
25°	549
35°	69
45°	7


Intensity	
Degree	CBCP
0°	1087
5°	1067
15°	890
25°	559
35°	187
45°	49

MXG2PRD3L130

Report #: ILL-20170427-03.002 (12)
 ILL-20170427-01.002 (24)
 ILL-20170427-04.002 (36)
 ILL-20170427-02.002 (50)

CCT MULTIPLIERS:

	82 CRI	92 CRI
2700K	(x 0.93)	(x 0.76)
3000K	(x 1.00)	(x 0.87)
3500K	(x 1.00)	(x 0.87)
4100K	(x 1.00)	(x 0.87)



Intensity	
Degree	CBCP
0°	17373
5°	12352
15°	569
25°	141
35°	38
45°	5

Intensity	
Degree	CBCP
0°	7842
5°	6897
15°	2035
25°	277
35°	18
45°	2

Intensity	
Degree	CBCP
0°	3239
5°	3108
15°	2013
25°	778
35°	97
45°	9

Intensity	
Degree	CBCP
0°	1540
5°	1511
15°	1260
25°	791
35°	264
45°	70


JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

MXG2PRD3L230

Report #: ILL-20170427-03.003 (12)
 ILL-20170427-01.003 (24)
 ILL-20170427-04.003 (36)
 ILL-20170427-02.0023(50)


CCT MULTIPLIERS:

	82 CRI	92 CRI
2700K	(x 0.93)	(x 0.76)
3000K	(x 1.00)	(x 0.87)
3500K	(x 1.00)	(x 0.87)
4100K	(x 1.00)	(x 0.87)




Watts: 20
 Lumens: 1365
 LPW: 68
 CCT: 3000K

Intensity	
Degree	CBCP
0°	20439
5°	14532
15°	669
25°	166
35°	45
45°	5




Watts: 20
 Lumens: 1526
 LPW: 76
 CCT: 3000K

Intensity	
Degree	CBCP
0°	9226
5°	8114
15°	2394
25°	326
35°	22
45°	3



Watts: 20
 Lumens: 1471
 LPW: 74
 CCT: 3000K

Intensity	
Degree	CBCP
0°	3811
5°	3656
15°	2368
25°	916
35°	115
45°	11



Watts: 20
 Lumens: 1274
 LPW: 64
 CCT: 3000K

Intensity	
Degree	CBCP
0°	1812
5°	1778
15°	1483
25°	931
35°	311
45°	82