







Electrical Data (Nominal Delivered Lumens)

L0	■ 650lm	1 3W
L1	∎ 1000lm	18W
L2	1400lm	22W

Finishes



Smart Lighting Solutions

- Industry leading dimming & color rendering
- 15°, 25° and 40° field changeable TIR optics
- Smooth flicker-free dimming down to 0.1%

The smart iQ Nano lighting solution features a 48V track system for individual luminaire addressability and group scene control. This feature rich luminaire provides high performance efficiency and light quality.

Built-In Intelligence

Powered by the Xicato XIM module with integrated beacon technology & energy consumption analytics

Maximum Control Capabilities

Wireless or DALI controllability via 48V DC track system for individual head addressability & group scene control

Design Meets Performance

Precise beam control & class leading color consistency in a sleek profile that blends into the track system

Xicato XIM Gen 4 Light Module

- Industry's best color consistency and reliability
- Individual light level adjustment
- Define groups and create scene settings
- Light management and performance monitoring
- Generate data reports logging temperature, intensity and supply voltage
- Bluetooth® Wireless control system with beacon technology
- Enabling services such as: indoor mapping, way finding and data collection

SMARTrack System

- 48V track system for intelligent track luminaires
- Low profile minimalistic track constructed of extruded aluminum in 4', 6' and 8' sections
- Recessed, surface, rigid or cable suspension mounting
- Works with DALI, 0-10V or BLE (bluetooth) enabled track luminaires
- Field cuttable and drillable
- Mounting clips included with recessed track



IQN 48V intelligent Track Mount



SMARTrack System Surface/Recessed



RA48-(75W) (200W) 48V Power Supply

