

iQNC

iQ Nano Canopy Luminaire with 48V Remote Power Supply

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

ELECTRICAL DATA

LED Light Engine	Wattage/Beam*	CCT / CRI	Nominal Delivered Lumens**
X1	13W (SP) / 10W (NF, FL)	3000K/82CRI	650lm
X2	18W (SP) / 15W (NF, FL)	3000K/82CRI	900lm/1000lm
X3	22W (NF, FL)	3000K/82CRI	1400lm

* Luminaire Wattage include driver and LED Module consumption. | ** Delivered lumens output will vary depending on CCT, CRI and optic selection.

FEATURES

- High quality Xicato LED (XIM Gen4)
- Smooth, flicker-free dimming
- Bluetooth wireless connectivity option
- Embedded intelligence with beacon technology and analytics (BLE only) Individually addressable luminaires (BLE or Dali option)

LED LIGHT ENGINE

- Xicato XIM Gen 4 Module
- Integrated LED chip with deep dimming driver, and embedded intelligence
- Choice of 83 or 97 CRI in 2700, 3000, 3500 & 4000K
- Color consistency of 1x2 MacAdam Ellipses 0-10V, bluetooth (BLE), and DALI options
- Self adjusts to avoid over temperature

OPTICS

- Dedicated 15° spot with field changeable 25° narrow flood & 40° flood

BLUETOOTH OPTION FEATURES ONLY (B10)

- Bluetooth low energy (BLE) 4.1 technology offers wireless connectivity via smart device (iOS or Android app)
- Windows based configurability and analytics
- Embedded beacon technology (Eddystone, iBeacon, and Alt Beacons) for location based information and wayfinding
- On board microprocessor stores LED performance data and power consumption
- Transmission range up to 400m, line of sight

DIMMING

Offers configurable logarithmic (default) or linear, smooth flicker free dimming in:

- 0-10V to 1%
- DALI to 0.1%
- BLE 0-10V to 1%

48V REMOTE POWER SUPPLY

48V remote power supply eliminates driver housing - can power multiple fixture, see power supply (sold separately) specifications for wattage restrictions.

MOUNTING

Mounts to a standard 4" octagon junction box

ACCESSORIES:



- Luminaire will accommodate (1) accessory
- Accessory holder required

LISTING/WARRANTY

- ETL Listed to US and Canadian standards for damp locations
- 5-Year Intense LED Limited Warranty



iQ



Horizontal Adjustability: 358°
Vertical Adjustability: 180°

BLUETOOTH (BLE) REFERENCE TOOLS

- [Xicato XIMtroller - UserGuide](#)
- [Xicato Control Panel - User Manual](#)

TRACK & REMOTE POWER SUPPLY SPECIFICATION LINKS

- [48V SMARTrack \(SMT\)](#)
- [48V 75W Power Supply \(RA48-75W\)](#)
- [48V 2x 100W Power Supply \(RA48-200W\)](#)

Example: IQNCX3-NF30D10W

Luminaire	Wattage / Optic	CCT / CRI ¹	Driver	Finish
IQNC	X1-SP (13W / 15° Spot)	27 (2700K/83 CRI XIM)	B10 (BLE 0-10V integral, 1%)	W (White)
	X1-NF (10W / 25° Narrow Flood)	279 (2700K/98 CRI XIM Artist)	DALI (DALI integral, 0.1%)	B (Black)
	X1-FL (10W / 40° Flood)	30 (3000K/83 CRI XIM)	D10 (0-10V integral, 1%)	SV (Silver)
	X2-SP (18W / 15° Spot)	309 (3000K/98 CRI XIM Artist)		
	X2-NF (15W / 25° Narrow Flood)	35 (3500K/83 CRI XIM)		
	X2-FL (15W / 40° Flood)	359 (3500K/98 CRI XIM Artist)		
	X3-NF (22W / 25° Narrow Flood)	40 (4100K/83 CRI XIM)		
	X3-FL (22W / 40° Flood)	409 (4100K/98 CRI XIM Artist)		

Accessories:

- LH50** (Accessory Holder)
- PFL16B** (Hex Louver, Black)
- PFL1** (Prismatic Spread Lens)
- PFL2** (Linear Spread Lens)
- PFL4** (Solite Lens)

Replacement Optics:

- IP-OP50NF** (25° Narrow Flood Optic)
- IP-OP50FL** (40° Flood Optic)

Notes:

- For other options, consult factory.

TRACK SYSTEM LUM-8905-24-P-3

INTENSE LIGHTING | 3340 E La Palma Ave, Anaheim, CA 92806 | tel 714 630-9877 | fax 714 630-9883

For Intense Lighting's limited product warranty, go to www.intenselighting.com. For a printed copy of the warranty, you may call 800 961-5321.

© 2024 Intense Lighting, LLC. All rights reserved. Note: This document is subject to change without notice.

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

IQNX2-SP30

Report #: ILL-20170505-07

IQNX3-NF30

Report #: ILL-20170505-05

IQNX3-FL30

Report #: ILL-20170505-06


LED Engine Multiplier:

IQNX1-SP30	(x 0.75)
IQNX2-SP30	(x 1.00)
IQNX1-NF30	(x 0.50)
IQNX2-NF30	(x 0.75)
IQNX3-NF30	(x 1.00)
IQNX1-FL30	(x 0.50)
IQNX2-FL30	(x 0.75)
IQNX3-FL30	(x 1.00)

CRI Multiplier:

IQNX1-SP30	(x 1.00)
IQNX1-SP309	(x 0.72)
IQNX2-SP30	(x 1.00)
IQNX2-SP309	(x 0.72)
IQNX1-NF30	(x 1.00)
IQNX1-NF309	(x 0.80)
IQNX2-NF30	(x 1.00)
IQNX2-NF309	(x 0.80)
IQNX3-NF30	(x 1.00)
IQNX3-NF309	(x 0.80)
IQNX1-FL30	(x 1.00)
IQNX1-FL309	(x 0.80)
IQNX2-FL30	(x 1.00)
IQNX2-FL309	(x 0.80)
IQNX3-FL30	(x 1.00)
IQNX3-FL309	(x 0.80)

15° Spot (X2-SP)




Watts: 18
Lumens: 893
LPW: 50
CCT: 3000K

Candelas at Nadir

Degree	Candela
0°	6233
5°	4980
15°	1120
25°	171
35°	80
45°	31

25° Narrow Flood (X3-NF)




Watts: 22
Lumens: 1315
LPW: 60
CCT: 3000K

Candelas at Nadir

Degree	Candela
0°	9923
5°	8887
15°	2955
25°	322
35°	41
45°	10

40° Flood (X3-FL)



Watts: 22
Lumens: 1410
LPW: 64
CCT: 3000K

Candelas at Nadir

Degree	Candela
0°	3326
5°	3198
15°	2031
25°	741
35°	205
45°	67