

# SS6CWD

6" SS LED Cylinder Warm Dim

Job Name		Catalog Number	
Notes		Type	

## ELECTRICAL DATA

WD2	System Wattage*	CCT / CRI	Nominal Delivered Lumens**
WD1	16.5W	3000K-1800K	1045lm
WD2	26.5W	3000K-1800K	1550lm

\* System Wattage includes driver and LED Module consumption.

\*\* Delivered lumen output will vary depending on CCT selection.

## FEATURES

- Dimming profile that warms as it dims, launching at 3000K at full intensity to 1800K at 1%
- Warm dim profile mimics the dimming curve of halogen—getting warmer as intensity decreases.

## LED LIGHT ENGINE

- 3000K to 1800K at 90 CRI
- 3 Step MacAdam (3 SDCM) binning within nominal CCTs
- 50,000 hours average rated life at 70% output

## ELECTRICAL SYSTEM

- Universal voltage 120-277V (347V available, consult factory)
- Osram Optotronic® standard with 0-10V dimming to 1%
- Power factor >9, 50/60Hz

## DIMMING

- EldoLED 0-10V 0.1% or 1%
- Lutron® LDE1 Hi-Lume 1% EcoSystem LED driver with Soft-on, Fade-to-Black dimming technology
- Lutron® LTEA2W Hi-Lume 1% 2-Wire LED driver (120V forward phase only)

## EMERGENCY BACKUP

Remote test switch included. External battery operates LED load of up to 7W at a minimum of 400 lumens for 90 minutes (EM7), or 20W at a minimum of 1250 lumens for 90 minutes (EM20).

## OPTICAL SYSTEM

Specification grade reflector with 1.2mm thickness. Reflector available in haze or white. Architectural, discrete polished self flange standard. Optional painted white flange is available. Meets RP-1 requirements with controlled light distribution at a 55° cut off.

## MOUNTING


- Ceiling mount for direct installation to 3" and 4" octagon junction box or 4" square junction box
- 144" Aircraft cable is supplied with complete canopy assembly. Aircraft cable is cuttable and can be modified in the field
- Wall mount bracket for installation to 4" octagon or square junction box
- Pendant stems supplied with complete canopy assembly. Pendant stems are cuttable and can be modified in the field.

## LISTING/WARRANTY




- ETL listed to US and Canadian standards for damp locations.
- 5-Year Intense LED Limited Warranty




## Surface Mount




## Wall Mount



## Pendant Mount



## Aircraft Cable



Canopy can be mounted at a maximum angle of 45°

Part Number (Example: SS6CWD2-WH2-P24)

Cylinder	LED Module	Dimming (120-277V)		Cylinder Finish	Reflector Finish	Mounting	Emergency Options	
SS6C	WD1 (16.5W / 3000K - 1800K)	blank	(0-10V Dimming 1%)	-W (White)	C (Clear)	-C144 (144" Aircraft Cable)	EM7 (7W Emergency Backup w/ Remote Test Switch <a href="#">IOTA part #ILB-CP07-A</a> )	
	WD2 (26.5W / 3000K - 1800K)	-ED10V1	(eldoLED 0-10V 1%)	-B (Black)	HZ ((Clear))	-P12 (12" Pendant)	EM20 (20W Emergency Backup w/ Remote Test Switch <a href="#">IOTA ILB-CP20-HE-S</a> )	
		-ED10V01	(eldoLED 0-10V 0.1%)	-SV (Silver)	W (Haze)	-P18 (18" Pendant)		
		-LUT1	(Lutron Hi-Lume 1%)		(White)	-P24 (24" Pendant)		
						-P36 (36" Pendant)		
						-P48 (48" Pendant)		
						-P96 <sup>3</sup> (96" Pendant)		
						-WB (Wall Bracket)		
						-S (Surface)		

# SS

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	

## SS6CWD1 / CLEAR

Report #: SS6CWD1\_C

Watts: 16.6  
Lumens: 1047  
LPW: 63  
CCT: 3000K


### Candelas at Nadir

Degree	CBCP
0°	1361
5°	1342
15°	1151
25°	665
35°	322
45°	51

### Reflector Finish Multipliers:

Haze (x 0.84)  
White (x 0.9)

### Illuminance at a Distance



## SS6CWD2 / CLEAR

Report #: SS6CWD2\_C

Watts: 26.3  
Lumens: 1554  
LPW: 59  
CCT: 3000K


### Candelas at Nadir

Degree	CBCP
0°	2021
5°	1993
15°	1709
25°	987
35°	476
45°	76

### Reflector Finish Multipliers:

Haze (x 0.84)  
White (x 0.9)

### Illuminance at a Distance



# DIMMING COMPATIBILITY


## 0-10V DIMMING

- 120V/277V
- Dims down to 1% or 0.1% light output
- Consult dimming manufacturer for installation instructions and power packs

## COMPATIBLE DIMMERS

Manufacturer	Part Number(s)
Hunt	PS-010-IV-120V, PS-010-WH-120V, PS-010-3W-IV-120, PS-010-3W-WH-120V, PS-010-IV-277V, PS-010-WH-277V, PS-010-3W-IV-277V, PS-010-3W-WH-277V, FD-010: PS-IFC-010-IV, PS-IFC-010-WH-120/277V, FD-010: PS-IFC-010-3W-IV, PS-IFC-010-3W-WH-120/277V, FD-010-120V, FD-010-277V
Leviton	Leviton Centura Fluorescent Control System, IllumaTech™ IP7 Series, DPSPE-212
Lightolier	ZP600FAM120, MP1500FAM120, V2000FAMU
Lithonia	LEQ BC, LEQ LVBC, SLD LVBC, SQ1DC
Lutron	DVT, NFTV
Synergy	ISD BC 120/277

JOB NAME		CATALOG NUMBER	
NOTES		TYPE	



## LUTRON HI-LUME® DIMMING

- 120V or 277V
- Dims down to 1%
- Consult dimming manufacturer for installation instructions

## COMPATIBLE DIMMERS

AYF-103P, AYF-103P-277, DVF-103, DVF-103P-277, DVSCF-103P, DVSCF-103P-277, HQRD-F6AN-DV, LXF-103PL, LXF-103PL-277, NF-10, NF-103P, NF-103P-277, NF-10-277, NTF-10, NTF-103P, NTF-103P-277, NTF-10-277, RRD-F6AN-DV, SF-12P-277-3, SF-103P, MAF-6AM, MAF-6AM-277, MCSF-6AM, MCSF-6AM-277, MRF2-F6AN-DV, SF-10P, SF-12P-277, SPSF-6A, SPSF-6A-277, SPSF-6AM, SPSF-6AM-277, VF-10, VTF-6AM

